

## 100M Industrial media converter with 4RJ45T



### Features

- Support 4 10/100M Ethernet and 1 FIBER Port(LC/FC/SC/ST Fiber Interface)
- Support IEEE802.1q, VLAN port isolation.
- Support IEEE802.3,IEEE802.3x,IEEE802.3u,F/H duplex, MDI/MDI-X auto negotiation.
- Designed for industrial applications. IP40 protection

### Specifications

RJ45 port rate	10/100BaseT(X) auto connection Full /Half duplex or force work mode support MDI/MDI-X connection
Fiber Connector	100BaseFX ports (SC/ST/FC/LC connector, optional)
Typical Distance	Single-mode: 20, 40,60, 80,100,120Km,optional Multi-mode: 2,5Km,optional
Power	24V DC, (9~36V DC)
Operation Temperature	-40° C to 80° C
Storage Temperature	-40° C to 80° C
Operation Humidity	5% to 95% (Non-condensing)
Case Dimension (W x D x H)	5% to 95% (Non-condensing)
Emission/Safety	60.5 x 118 x 140 mm
Casing	FCC Class A, CE Class A
Installation	IP40 protection, Aluminium Alloy
Warranty	2-Year Warranty

### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-MCI-10/100-MM02	2KM Dual-fiber MM 1310NM SC
TL-MCI-10/100-SM20	20KM Dual-fiber SM 1310NM SC
TL-MCI-10/100-SM40	40KM Dual-fiber SM 1310NM SC
TL-MCI-10/100-SM60	60KM Dual-fiber SM 1310NM SC
TL-MCI-10/100-SM80	80KM Dual-fiber SM 1310NM SC
TL-MCI-10/100BiDi-SM20	20KM BiDi SM1310/1550NM SC
TL-MCI-10/100BiDi-SM40	40KM BiDi SM1310/1550NM SC
TL-MCI-10/100BiDi-SM60	60KM BiDi SM1310/1550NM SC
TL-MCI-10/100BiDi-SM80	80KM BiDi SM1310/1550NM SC