

KVM - P1716

KVM-P1716 is the KVM console which is mounted in 1U of rack space, which is operated with several computers by integrated LCD, Keyboard, Touch pad Mouse. Saving the cost which is configured for each computer keyboard, mouse, monitor separately and their space. It can connect and control 16 hosts directly and support the multiple hardware platforms and operating systems.



Switch Function

Features

- 17" A grade TFT LCD panel, high brightness, high definition, high resolution display
- PS2 thinness Keyboard with 99 keys
- Touch pad mouse, high-resolution, high sensitivity, 2 functional keys and scroll wheel functions, PS/2 standard interface

Switch Function

- Can be connected to 16 computers directly and achieve switching operations
- Alarm tone prompts to switch to complete
- No need to install additional software, switch between multiple computers easily through the OSD menu or hot key operation.
- Will automatically record and store the original working condition of keyboard, mouse when switching computer.
- The mouse can be used normally in the automatic scanning mode.
- DDC emulation the video setting of each server will be automatically adjusted to the best display.
- Can finish the switching function between the host by using the mouse.
- With a hot swap function (add or remove hosts directly without having to turn off the KVM
- Product Specification

KVM SWITCH

Specifications

| | | |
|---------------------------------------|-----------------------|---|
| TFT LCD | LCD Type | XGA TFT |
| | Display Area | 17" |
| | Resolution | 1280x1024@60Hz |
| | Color | 16.7 M |
| | Lumianance | 300 cd/m2 |
| | Contrast Ratio | 500:1 |
| | Back Light | 4-CCFLs |
| | Pixels Intervals (mm) | 0.264(H)x0.264(W) |
| | LCD MTBF | >50,000 hrs |
| | LCD Power | 1 x Switch |
| Key Board | Keys | 99 keys (82 Keys +17 independent Number keys) |
| | Compatible IBM/AT | Support Windows 9X/Me/NT/2000/XP |
| | Interface | PS/2 or USB |
| | MTBF | >10,000,000 Time |
| Mouse | X/Y Resolution | >1000 Point/Inch |
| | Hardware Interface | PS/2 or USB |
| | Wheel | Support Wheel Function |
| | OS | Support Windows 9X/Me/NT/2000/XP |
| | MTBF | >1,000,000 Times |
| Switch | PC Connection Ports | 16 Ports (Integrated signal input end of VGA/Keyboard/Mouse) |
| | PC Selection | OSD Menu, Hot Key |
| | Auto Scan Intervals | 5-99 Sec |
| Power Supply | AC | 90V-264V AC/Double Output(Max): 34.8W |
| | DC | -36V-72V DC/Double Output(Max): 34.8W |
| | MTBF | >60,000 hrs (25 degree) |
| Net Weight | | 14.9Kg |
| Unit Dimensions (WxDxH) | | 448mm x 601mm x 42.5mm |
| Working Temperature/Store Temperature | | 0-50 degree/ -20-60 egree |
| Humidity | | 0-80%. Non - Condensing |

KVM SWITCH

ORDERING INFORMATION

| PART NUMBER | DESCRIPTION |
|-------------|--|
| TL-KVM-1716 | 16 Port KVM Console integrated LCD, Keyboard, and Touch pad mouse. |