

FIBER OPTIC PIGTAILS

Single Mode Pigtails

Techlogiks Single Mode fiber pigtails are available in a variety of colours to complement any network, custom configurations and performances. Full choice of available connector types like LC/SC/ST/FC/E2000/MTRJ etc..



Features

- 100% optically tested in factory
- Tight or semi-tight buffered 900um cable available
- Visual inspection of endface by 400x microscope.
- Low insertion loss and back reflection.

Specifications

Connector Type	SC,ST,FC,LC,MTRJ,MU
Fiber Type	G652D, G655, G657A1/A2, G657B2
Insertion Loss (Against Ref) IEC 61300-3-4	< 0.30 dB
Return Loss	> 50.0 dB (UPC)
	> 60.0 dB (APC)
Endface	100% passed GR-326-CORE Section 4.4.5 Endface Geometry Requirements***
Durability IEC 61300-2-2	< 0.20 dB (500 cycles)
Operating Temperature	-20°C to +70°C

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-FPT-SC-09-1.5	SC Single Mode Fiber Optic Pigtail 1.5 Meter
TL-FPT-SC/APC-09-1.5	SC/APC Single Mode Fiber Optic Pigtail 1.5 Meter
TL-FPT-LC-09-1.5	LC Single Mode Fiber Optic Pigtail 1.5 Meter
TL-FPT-LC/APC-09-1.5	LC/APC Single Mode Fiber Optic Pigtail 1.5 Meter
TL-FPT-XX-09-YYY	
XX –LC or SC or ST or FC or MTRJ, YY – 001, 002, 003 Meters etc....	