

**Lock**



**Features**

- Name: cabinet lock.
- Specifications: round lock (optional).
- Surface treatment: spray.
- Characteristics: the key to universal.
- Mounting position: the cabinet front door, back door and side door.

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-LK	Cabinet Lock

**Digital Temperature Unit**



**Features**

- Power supply: 85-265VAC.
- Sensor: International cu50 resistance.
- Measuring range: -20—80.
- Measurement accuracy: 1.0(+/-1.0%).
- Sampling rate: 2/second.
- Output form: double relays(one group for master control, another one for alarm).
- Sensor's differential gap adjustable.
- Sensor support open circuit alarm.
- Power consumption: <5W.
- Ambient temperature: -10-50

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-DTU	Digital Temperature Unit

**Power Distribution Unit**



**Features**

- Rating Voltage: 250VAC 50/60Hz
- Socket Quantity: 6 Way, 10 Way
- Rating Current: 13 Amps
- Max. Power: 3250W
- Socket and Plug : UK Type
- Mounting Type : 6 Way - Horizontal, 10 Way - Vertical
- 19" Rack mountable 6 way PDU
- CE Approved : Yes
- Surge Protection: No
- RoHS : Yes
- Industrial PDU's are also available

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-PDU6	6 Way PDU, 1U, 2 Meter Cable
TL-CAC-PDU10	10 Way PDU, 1U, 2 Meter Cable

## 16Amp Industrial Type Power Distribution Unit – 12 Way



**IEC60309 plug (16A 2P+E)**

Specification	
Item	Detailed Description
Socket Type	BS1363(90degree) Outlet Module [12];
Socket Quantity	12 way
Power Input	Left end single input
Bracket Install	Inverse installation
Cable with plug	IEC60309 plug (16A 2P+E)
Control Function	No controlling function
Protection Function	No protecting function
Case	Black



Cable Specification	3 x 2.5 mm <sup>2</sup> x 3M
Product Size	L x W x H = 820 x 44.4 x 62 mm
Mounting Length	795 mm
Case Length	768 mm
PDU Exponent	1.709
Fittings	2pcs $\phi$ 6x16mm cross bolt, 2pcs M6 float nut, PDU manual
Rating voltage	250VAC 50/60Hz
Rating Current	16A
Max. Power	4000W
Safety Authentication	CE, RoHS
Interior Connection Wire	1.5 mm <sup>2</sup>
Interior Connection Style	Group connection
Fix the Cable	Small cable clamp

**Ordering Information**

<b>Part Number</b>	<b>Description</b>
TL-CAC-PDU12-16A-IND	12 Way, 16Amp, Industrial Type Power Distribution Unit, 3.0mtr cable length

POWER DISTRIBUTION UNIT

### 32Amp Industrial Type Power Distribution Unit – 12 Way



**IEC60309 plug (32A 2P+E)**

POWER DISTRIBUTION UNIT

Specification	
Item	Detailed Description
Socket Type	BS1363(90degree) Outlet Module [12];
Socket Quantity	12 way
Power Input	Left end single input
Bracket Install	Inverse installation
Cable with plug	IEC60309 plug (32A 2P+E)
Control Function	No controlling function
Protection Function	No protecting function
Case	Black



Cable Specification	3 x 2.5 mm <sup>2</sup> x 3M
Product Size	L x W x H = 860 x 44.4 x 62 mm
Mounting Length	835 mm
Case Length	808 mm
PDU Exponent	1.709
Fittings	2pcs φ6×16mm cross bolt, 2pcs M6 float nut, PDU manual
Rating voltage	250VAC 50/60Hz
Rating Current	32A
Max. Power	8000W
Safety Authentication	CE, RoHS
Interior Connection Wire	2.5 mm <sup>2</sup>
Interior Connection Style	Group connection
Fix the Cable	Cable clamp

**Ordering Information**

<b>Part Number</b>	<b>Description</b>
TL-CAC-PDU12-32A-IND	12 Way, 32Amp, Industrial Type Power Distribution Unit, 3.0mtr cable length

POWER DISTRIBUTION UNIT