

KVM - P1708

KVM-P1708 is the KVM console which is mounted in 1U of rack space, which is operated with several computers by integrated LCD, Keyboard, Touch pad Mouse. Saving the cost which is configured for each computer keyboard, mouse, monitor separately and their space. It can connect and control 8 hosts directly and support the multiple hardware platforms and operating systems.



Features

- 17" A grade TFT LCD panel, high brightness, high definition, high resolution display
- PS2 thinness Keyboard with 99 keys
- Touch pad mouse, high-resolution, high sensitivity, 2 functional keys and scroll wheel functions, PS/2 standard interface
- Designed for industrial applications. IP40 protection

Switch Function

- Can be connected to 8 computers directly and achieve switching operations
- Alarm tone prompts to switch to complete
- No need to install additional software, switch between multiple computers easily through the OSD menu or hot key operation.
- Will automatically record and store the original working condition of keyboard, mouse when switching computer.
- The mouse can be used normally in the automatic scanning mode.
- DDC emulation the video setting of each server will be automatically adjusted to the best display.
- Can finish switching function between the host by using the mouse.
- With a hot swap function (add or remove hosts directly without having to turn off the KVM)

Specifications

TFT LCD	LCD Type	XGA TFT
	Display Area	17"
	Resolution	1280x1024@60Hz
	Color	16.7 M
	Lumianance	300 cd/m2
	Contrast Ratio	500:1
	Back Light	4-CCFLs
	Pixels Intervals (mm)	0.264(H)x0.264(W)
	LCD MTBF	>50,000 hrs
	LCD Power	1 x Switch
Key Board	Keys	99 keys (82 Keys +17 independent Number keys)
	Compatible IBM/AT	Support Windows 9X/Me/NT/2000/XP
	Interface	PS/2 or USB
	MTBF	>10,000,000 Time
Mouse	X/Y Resolution	>1000 Point/Inch
	Hardware Interface	PS/2 or USB
	Wheel	Support Wheel Function
	OS	Support Windows 9X/Me/NT/2000/XP
	MTBF	>1,000,000 Times
Switch	PC Connection Ports	8 Ports (Integrated signal input end of VGA/Keyboard/Mouse)
	PC Selection	OSD Menu, Hot Key
	Auto Scan Intervals	5-99 Sec
Power Supply	AC	90V-264V AC/Double Output(Max): 31.2W
	DC	-36V-72V DC/Double Output(Max): 31.2W
	MTBF	>60,000 hrs (25 degree)
Net Weight	14.7Kg	
Unit Dimensions (WxDxH)	448mm x 601mm x 42.5mm	
Working Temperature/Store Temperature	0-50 degree/ -20-60 egree	
Humidity	0-80%. Non - Condensing	

KVM SWITCH

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-KVM-1708	8 Port KVM Console integrated LCD, Keyboard, and Touch pad mouse.